

**Coordination Parameters VBY W23
(Rev VBY 20230427)**

TERMINAL CAPACITY:

-Pax terminal departure flow max 500 pax/hr rolling

Cabin Factor		
Flight Type	Percent	Frequency
Charter	95%	Season
Regular	80%	Season

RUNWAY (BOARDING GATE) CAPACITY:

-Total 01 departure per 5 min/rolling

DE-ICE CAPACITY (DEC-MAR):

-Total 02 departure per 20 min/rolling

AIR SPACE CAPACITY:

-Total 09 arrivals per 60 min/rolling

CHARTER SEPARATION:

-90- min separation between Charter flights

STANDS CAPACITY:

-10- min buffer between each aircraft operation per stand

AIRCRAFT SEPARATION:

-30- min separation between following A/C: 739, 738, 73G, 736, 735, 734, 733, 732, 731, 717, M81, M82, M83, M87, M90, 321, 320, 319, 318

AIRCRAFT DIVISION/STANDS:

STANDS 2 AND 3:

ATP, 739, 738, 73G, 736, 735, 734, 733, 732, 731, 717, M81, M82, M83, M87, M90, 321, 320, 319, 318, E90, E95, CR9, F100

STAND 8:

ATP, AT4, AT7, S20, F50, CR1, CR2, CR7, DH7, DH8, ER3, ER4, E70, E75, E90, D38, FRJ, F70

STAND 4:

CR9

STAND 7:

AR1, AR7, AR8, AT4, AT7, S20, F50, CR1, CR2, CR7, CR9

STANDS 1,2,3,4 AND 5:

AR1, AR7, AR8, AT4, AT7, S20, F50, CR1, CR2, CR7, DH7, DH8, ER3, ER4, E70, E75, D38, FRJ, F70

STANDS 1, 2, 3, 4, 5, 7 AND 8:

SF3, J31, J32, J41, CNC, DHT, SWN, BEC

STANDS 9 AND 10:

J31, J32, J41, CNC, DHT, SWN, BEC